



SUPERWAY TIRES

2024



SUPERWAY

Table of Contents

6.50R16LT	03	275/80R22.5	22
7.00R16LT	04	9R22.5	22
7.50R16LT	05	10R22.5	22
8.25R16LT	06	11R22.5	23
8.25R20	06	11R24.5	25
9.00R20	07	12R22.5	26
12.5R20	07	13R22.5	27
14.00R20	08	285/75R24.5	28
16.00R20	08	295/75R22.5	29
10.00R20	09	295/60R22.5	29
11.00R20	11	315/60R22.5	30
12.00R20	13	315/70R22.5	30
12.00R24	15	295/80R22.5	31
8R17.5	16	315/80R22.5	33
8.5R17.5	16	385/55R22.5	35
10R17.5	16	385/65R22.5	35
9.5R17.5	17	445/65R22.5	36
215/75R17.5	17	445/45R19.5	36
235/75R17.5	18	425/65R22.5	36
225/80R17.5	18	335/80R20MPT	37
245/70R19.5	19	365/80R20	37
225/70R19.5	19	325/95R24	37
265/70R19.5	20	395/85R20	38
285/70R19.5	20	425/85R21	38
255/70R22.5	21	31*12.5R16.5LT	38
275/70R22.5	21		

GOOD QUALITY GOST-EFFECTIVE

SPUREWAY TRUCK / BUS TIRES

FEEL FREE TO CHOOSE

- Various sizes/patterns for different markets
- Ready stock for popular sizes
- Prompt lead time



6.50R16LT



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A860	5.5F	12PR	110/105	M	9.5	1060/925	670
A801	5.5F	12PR	110/105	M	9.5	1060/925	670
A828	5.5F	12PR	110/105	K	10.5	1060/925	670
A866	5.5F	10PR	107/102	L	9.7	975/850	560

7.00R16LT



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A860	5.5F	14PR	118/114	M	11	1320/1180	770
A801	5.5F	14PR	118/114	M	11	1320/1180	770
A828	5.5F	14PR	118/114	K	11.5	1320/1180	770
A866	5.5F	12PR	115/110	M	9.7	1215/1060	670
A829	5.5F	14PR	118/114	K	16	1320/1180	770

7.50R16LT



A857



A866



A502



A801



A807



A808



A812

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A857	6.00G	14PR	122/118	M	15	1500/1320	770
A866	6.0G	14PR	122/118	L	10.5	1500/1320	770
A502	6.00G	16PR	125/121	M	12.6	1650/1450	870
A801	6.00G	14PR	122/118	K	12.0	1500/1320	770
A807	6.00G	14PR	122/118	K	12	1500/1320	770
A808	6.00H	14PR	122/118	K	15	1500/1320	770
A812	6.00H	14PR	122/118	K	14.5	1500/1320	770

8.25R16LT



A801



A807



A808



A812

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A801	6.50H	16PR	128/124	K	13.0	1800/1600	770
A807	6.50H	16PR	128/124	K	13	1800/1600	770
A808	6.50H	16PR	128/124	K	16.5	1800/1600	770
A812	6.50H	16PR	128/124	K	15.0	1800/1600	770

8.25R20



A801



A812

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A801	6.50	16PR	139/137	K	15.5	2430/2300	900
A812	6.50H	16PR	139/137	K	16.5	2430/2300	930

9.00R20



A801



A807



A808



A812

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A801	7.00	16PR	144/142	K	15.5	2800/2650	900
A807	7.00	16PR	144/142	K	15.5	2800/2650	900
A808	7.00	16PR	152/149	K	16.5	2800/2650	900
A812	7.00	16PR	144/142	K	16.5	2800/2650	900

12.5R20



A891

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A891	11.00	18PR	145	L	16.9	3250	650

14.00R20



A857



A859

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A857	10.00	20PR	164/161	J	20	4625/4250	690
A859	10.00	20PR	164/161	J	20	5000/4625	790

16.00R20



A859

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A859	11.25	22PR	174/171	G	20.5	6700/6150	760

10.00R20



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(lb)	PRESSURE(kpa)
A801G+	7.50	18PR	149/146	K	16.5	3250/3000	930
A801	7.50	18PR	149/146	K	16.5	3250/3000	930
A807	7.50	18PR	149/146	K	16	3250/3000	930
A808	7.50	18PR	149/146	K	18.5	3250/3000	930
A809	7.50	18PR	149/146	G	18.0	3250/3000	930
A812	7.50	18PR	149/146	K	18.5	3250/3000	930
AX831	7.50	18PR	149/146	K	16.4/16.9	3250/3000	930
AX808	7.50	18PR	149/146	J	17.9	3250/3000	930
AX833	7.50	18PR	149/146	F	22.4	3250/3000	930

11.00R20



A801



A807



A808



A809



A812



A815



A835



AX831



AX808



AX833

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
A801	8.00	18PR	152/149	K	17.0	3550/3250	930
A807	8.00	18PR	152/149	K	16.5	3550/3250	930
A808	8.00	18PR	152/149	K	19.5	3550/3250	930
A809	8.00	18PR	152/149	G	20.5	3550/3250	930
A812	8.00	18PR	152/149	K	20.5	3550/3250	930
A815	8.00	18PR	152/149	G	20.5	3550/3250	930
A835	8.00	18PR	152/149	K	15.5	3550/3250	930
AX831	8.00	18PR	152/149	K	16.4/16.9	3550/3250	930
AX808	8.00	18PR	152/149	K	17.9	3550/3250	930
AX833	8.00	18PR	152/149	F	24.7	3550/3250	930

12.00R20



A801



A807



A808



A809



A811



A812



A815



A833



A817



AX831



AX808



AX833

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
A801L	8.50	20PR	156/153	K	16	4000/3650	900
A801	8.50	20PR	156/153	K	17.5	4000/3650	900
A807	8.50	20PR	156/153	K	17.5	4000/3650	900
A808	8.50	20PR	156/153	K	20.5	4000/3650	900
A809	8.50	20PR	156/153	G	22.5	4000/3650	900
	8.50	22PR	158/155	G	22.5	4250/3875	970
A811	8.50	20PR	156/153	G	22.5	4000/3650	900
A812	8.50	20PR	156/153	J	21.5	4000/3650	900
A815	8.50	20PR	156/153	G	22.5	4000/3650	900
A833	8.50	20PR	156/153	G	22.5	4000/3650	900
A817	8.50	20PR	156/153	G	22.5	4000/3650	900
AX831	8.50	20PR	156/153	K	16.4/16.9	4000/3650	900
AX808	8.50	20PR	156/153	J	17.9	4000/3650	900
AX833	8.50	20PR	156/153	F	24.7	4000/3650	900

12.00R24



A801



A807



A829



A817



A582

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A801C	8.50	20PR	160/157	K	15.5	4500/4125	900
A807	8.50	20PR	160/157	K	16	4500/4125	900
A829	8.50	20PR	160/157	K	18.5	4500/4125	900
A817	8.50	20PR	160/157	K	18.5	4500/4125	900
A582	8.5	20	160/157	K	18.0	4500/4125	900

8R17.5



A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A852	6.00	12PR	121/120	M	11.5	1450/1400	625

8.5R17.5



A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A852	6.00	12PR	121/120	M	11.5	1450/1400	625

10R17.5



A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A852	7.5	16PR	143/141	J	13	2725/2527	860

9.5R17.5



A851



A837



A838



A829

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A851	6.75	18PR	143/141	J	13.6	2725/2575	875
A829	6.75	18PR	142/141	J	15.9	2725/2575	875
A837	6.75	18PR	143/141	J	14.5	2725/2575	875
A838	6.75	18PR	143/141	J	16	2725/2575	875

215/75R17.5



A852



A855



A516

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A852	6.00	18PR	135/133	J	13	2180/2060	860
A855	6.00	16PR	135/133	J	13.6	2180/2060	865
A516	6.00	16PR	135/133	K	12.1	2180/2060	865

235/75R17.5



A852



A855



A516

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A852	6.75	18PR	143/141	J	13	2725/2527	860
A855	6.75	18PR	143/141	J	13.6	2725/2575	865
A516	6.75	18PR	143/141	K	12.1	2725/2575	865

225/80R17.5



A510

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A510	6.75	16PR	123/122	L	15.6	1550/1500	700

245/70R19.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A851	7.50	16PR	135/133	L	13	2180/2060	830
A855	7.50	14PR	133/131	L	15	2060/1950	760

225/70R19.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A851	6.75	14PR	128/126	M	13	1800/1700	760
A855	6.75	14PR	128/126	L	15	1800/1700	760

265/70R19.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A855	7.50	16PR	143/141	J	17.5	2727/2575	850
A516	7.50	16PR	140/138	M	12.6	2500/2360	775
A837	7.50	18PR	143/141	J	14.5	2727/2575	850
A838	7.50	18PR	143/141	J	17.5	2727/2575	850

285/70R19.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A837	8.25	18PR	150/148	J	14.5	3350/3150	900
A838	8.25	18PR	150/148	J	17.0	3350/3150	900

255/70R22.5



A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A852	7.50	16PR	140/137	N	10.5	2500/2300	830

275/80R22.5



A855



A506

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A855	8.25	18PR	149/146	M	17.4	3250/3000	900
A506	8.25	18PR	149/146	M	14.6	3250/3000	900

275/70R22.5



A852



A853



A809



A832

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A852	8.25	16PR	148/145	M	13	3150/2900	900
A853	8.25	16PR	148/145	K	20.5	3150/2900	900
A809	8.25	16PR	148/145	G	20.5	3150/2900	900
A832	8.25	16PR	148/145	M	20.5	3150/2900	900

9R22.5



A858

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A858	6.75	14PR	136/134	L	14.5	2240/2120	760

10R22.5



A851



A858

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A851	7.50	16PR	144/142	L	15.1	2800/2650	900
A858	7.50	16PR	144/142	M	15	2800/2650	790

11R22.5



A854



A863A



A801



A850



A826



A803



A511



A512



A878



A825



A822



A824



A802



A809



A810



A816



A832

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
A854	8.25	18PR	151/148	G	20.4	3450/3150	930
A863A	8.25	16PR	146/143	L	20.5	3000/2725	830
A801	8.25	18PR	149/146	L	14.5	3250/3000	930
	8.25	18PR	151/148	K	15.5	3450/3150	930
A803	8.25	18PR	151/148	K	17	3450/3150	930
	8.25	20PR	152/149	M	17	3550/3250	930
A511	8.25	18PR	146/143	M	14.1	3450/3150	930
A512	8.25	18PR	151/148	K	19.4	3450/3150	930
A878	8.25	18PR	151/148	L	14.5	3250/3000	930
A825	8.25	16PR	146/143	M	15.5	3000/2725	830
A822	8.25	16PR	146/143	M	10.5	3000/2725	830
A824	8.25	16PR	146/143	M	10.5	3000/2725	830
A802	8.25	18PR	151/148	K	18.5	3450/3150	930
A809	8.25	18PR	151/148	G	20.5	3450/3150	930
A810	8.25	18PR	151/148	G	20.5	3450/3150	930
A816	8.25	18PR	151/148	K	16.5	3450/3150	930
A832	8.25	18PR	151/148	K	20.5	3450/3150	930
A850	8.25	18PR	151/148	K	18	3450/3150	930
A826	8.25	16PR	146/143	L	20.5	3000/2725	830

11R24.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
A825	8.25	16PR	149/146	M	15.5	3250/3000	830
A822	8.25	16PR	149/146	M	10.5	3250/3000	830
A826	8.25	16PR	149/146	L	20.5	3250/3000	830

12R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
A854	9.00	18PR	152/149	G	20.5	3350/3250	930
A803	9.00	18PR	152/149	K	17	3550/3250	930
A801	9.00	18PR	152/149	K	15.5	3550/3250	930
A802	9.00	18PR	152/149	K	18.5	3550/3250	930
A809	9.00	18PR	152/149	G	20.5	3550/3250	930
A816	9.00	18PR	152/149	K	16.5	3550/3250	930
A832	9.00	18PR	152/149	K	20.5	3550/3250	930
A850	9.00	18PR	152/149	K	18	3550/3250	930

13R22.5



A801



A869



A803



A816



A802



A809



A832



A850

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A801	9.75	18PR	154/151	K	15.5	3750/3450	830
A869	9.75	18PR	154/151	K	15.5	3750/3450	830
A803	9.75	18PR	154/151	K	18.5	3750/3450	830
A816	9.75	18PR	154/151	K	17.5	3750/3450	830
A802	9.75	18PR	154/151	K	18.5	3750/3450	830
A809	9.75	18PR	154/151	G	20.5	3750/3450	830
A832	9.75	18PR	154/151	K	20.5	3750/3450	830
A850	9.75	18PR	154/151	K	18.5	3750/3450	830

285/75R24.5



A822



A825



A826



A819

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A825	8.25	16PR	147/144	M	15.5	3075/2800	830
A822	8.25	16PR	147/144	M	10.5	3075/2800	830
A819	8.25	16PR	147/144	L	20.5	3075/2800	830
A826	8.25	16PR	147/144	L	20.5	3075/2800	830

295/75R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A863A	9.00	16PR	146/143	L	20.5	3000/2725	830
A825	9.00	16PR	146/143	M	15.5	3000/2725	830
A822	9.00	16PR	146/143	M	10.5	3000/2725	830
A819	9.00	16PR	146/143	L	20.5	3000/2725	830
A826	9.00	16PR	146/143	L	20.5	3000/2725	830

315/60R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A851	9.75	18PR	151/148	L	14.5	3650/3350	900
AX865	9.75	20PR	153/150	K	22.0	3550/3250	900
A802	9.75	18PR	152/148	L	17.9	3550/3150	900

315/70R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A851	9.00	18PR	151/148	M	14.5	3450/3150	830
A853	9.00	18PR	151/148	M	19	3450/3150	830

295/60R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A851	9.00	18PR	150/147	K	16	3350/3075	900
A853	9.00	18PR	150/147	K	19	3350/3075	900

295/80R22.5



A854



A862



A861



A803



A703



A801



A802



A809



A832



AX510



AX865

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
A854	9.00	18PR	152/149	G	20.5	3550/3250	900
A862	9.00	18PR	152/149	M	14.5	3550/3250	900
A861	9.00	18PR	152/149	M	15	3550/3250	900
A803	9.00	18PR	152/149	K	17	3550/3250	900
A703	9.00	18PR	152/149	K	15.00	3550/3280	900
A801	9.00	18PR	152/149	K	15.5	3550/3250	900
A802	9.00	18PR	152/149	K	18.5	3550/3250	900
A809	9.00	18PR	152/149	G	20.5	3550/3250	900
A832	9.00	18PR	152/149	K	20.5	3550/3250	900
AX510	9.00	20PR	154/149	L	16.4	3750/3250	850
AX865	9.00	18PR	152/149	L	20.4	3550/3250	900

315/80R22.5



A801



A878



A802



A869



A803



A809



A832



A701



A823



A813



A880



A853



A854

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kPa)
A853	9.00	20PR	157/154	L	20.5	4125/3750	900
A854	9.00	20PR	157/154	J	20.5	4125/3750	900
A854PLUS	9.00	20PR	157/154	J	23.5	4125/3750	900
A880	9.00	20PR	157/154	L	16.5	4125/3750	900
A801	9.00	20PR	157/154	K	15	4125/3750	830
A801A	9.00	20PR	157/154	K	15	4125/3750	830
A801C+	9.00	20PR	157/154	K	15	4125/3750	830
A803	9.00	20PR	157/154	K	17	4125/3750	900
A701	9.00	20PR	157/154	K	14.5	4125/3750	830
A878	9.00	20PR	157/154	L	14.5	4125/3750	900
A802	9.00	20PR	157/154	K	18.5	4125/3750	900
A823	9.00	20PR	157/154	K	14.5	4125/3750	830
A809	9.00	20PR	157/154	G	20.5	4125/3750	900
A813	9.00	20PR	157/154	K	17.5	4125/3750	830
A832	9.00	20PR	157/154	K	20.5	4125/3750	900
A869	9.75	20PR	153/150	K	22.0	3550/3250	900

385/55R22.5



A864

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A864	12.25	20PR	160	K	15.5	4500	900

445/45R19.5



A890

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A890	6.00G	10PR	118/116	L	11.5	1320/1250	590

385/65R22.5



A806



A861



A836



A507



A805

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A806	11.75	20PR	160	K	16	4500	900
A861	11.75	20PR	160	K	16	4500	900
A836	11.75	20PR	160	K	16.5	4500	900
A507	11.75	24PR	164	J	17.4	5000	930
A805	11.75	20PR	160	K	16	4500	900

445/65R22.5



A856

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A856	13.00	20PR	168	L	18	5600	830

425/65R22.5



A856



A503

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A856	13.00	20PR	165	K	18	5150	830
A503	13.00	20PR	165	J	15.9	5150	825

335/80R20MPT



A879

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A879	11.00	18PR	149	K	16.9	3250	650

395/85R20



A859

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A859	10.00	14PR	158	J	25	4250	660

365/80R20



A859

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A859	10.00	16PR	160	K	20	4500	900

425/85R21



A875

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A875	10.00	24PR	167	D	24	6100	550

325/95R24



SP505

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
SP505	9.00	22PR	162/160	K	15.9	4750/4500	850

31*12.5R16.5LT



A889

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
A889	8.25	10PR	134	N	14.1	2120	450