



SUPERWAY

**TRUCK / BUS TIRES
PRODUCT CATALOGUE**



GOOD QUALITY COST-EFFECTIVE

20⁺

More than 20 years
tires experience

100⁺

More than 100
countries and regions

550⁺

More than 550 tire sizes

5000000⁺

More than 5 million tires
exported annually

SINCERELY HOPE TO ESTABLISH A LONG-TERM AND
MUTUALLY BENEFICIAL COOPERATIVE RELATIONSHIP WITH YOU

[illegible]

TBR ----Table of Contents

7.50R15LT	06	14.00R20	26
6.50R16LT	06	16.00R20	27
7.00R16LT	07	12.5R20	26
7.50R16LT	08	335/80R20MPT	27
8.25R16LT	09	365/80R20	27
9.00R16	09	395/85R20	28
255/100R16LT	10	425/85R21	28
37×12.5R16.5LT	10	9R22.5	34
8R17.5	11	10R22.5	34
8.5R17.5	11	11R22.5	29
9.5R17.5	12	12R22.5	31
10R17.5	12	13R22.5	33
205/75R17.5	13	255/70R22.5	34
215/70R17.5	13	275/70R22.5	35
215/75R17.5	14	275/80R22.5	35
225/80R17.5	14	295/60R22.5	36
235/75R17.5	15	295/75R22.5	36
245/70R17.5	16	295/80R22.5	37
225/70R19.5	16	315/60R22.5	41
245/70R19.5	17	315/70R22.5	41
265/70R19.5	17	315/80R22.5	39
285/70R19.5	18	385/55R22.5	42
435/50R19.5	18	385/65R22.5	42
445/45R19.5	18	425/65R22.5	43
7.50R20	26	445/50R22.5	43
8.25R20	25	445/65R22.5	43
9.00R20	25	12.00R24	44
10.00R20	19	325/95R24	45
11.00R20	21	11R24.5	46
12.00R20	23	285/75R24.5	45

7.50R15LT



A801

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A801	6.00G	14PR	121/117	L	13	774	215	1450/1285	760

6.50R16LT



A860



A801



A828



A866

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A860	5.5F	12PR	110/105	M	9.5	750	185	1060/925	670
A801	5.5F	12PR	110/105	M	9.5	750	185	1060/925	670
A828	5.5F	12PR	110/105	K	10.5	748	182	1060/925	670
A866	5.5F	10PR	107/102	L	11	750	185	975/850	560

7.00R16LT



A860



A801



A828



A866



A829

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A860	5.5F	14PR	118/114	M	11.0	775	200	1320/1180	770
A801	5.5F	14PR	118/114	M	11.0	775	200	1320/1180	770
A828	5.5F	14PR	118/114	K	11.5	775	196	1320/1180	770
A866	5.5F	12PR	115/110	M	9.7	775	200	1215/1060	670
A829	5.5F	14PR	118/114	K	16.0	775	196	1320/1180	770

7.50R16LT



A857



A801



A866



A502



A801



A807



A808



A812



A833

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A857	6.00G	8PR	112/107	M	10.0	805	215	1120/975	450
A801	6.00G	16PR	125/121	M	11.2	805	215	1650/1450	870
A866	6.00G	14PR	122/118	L	10.5	805	215	1500/1320	770
A502	6.00G	16PR	125/121	M	11.2	805	215	1650/1450	870
A801	6.00G	14PR	122/118	K	12.0	805	210	1500/1320	770
A807	6.00G	14PR	122/118	K	12.0	800	210	1500/1320	770
A808	6.00H	14PR	122/118	K	15.0	805	215	1500/1320	770
A812	6.00H	14PR	122/118	K	14.5	805	210	1500/1320	770
A833	6.00G	14PR	122/118	L	14.5	815	215	1500/1320	770

8.25R16LT



A801



A807



A808



A812



A833

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A801	6.50H	16PR	128/124	K	13.0	855	230	1800/1600	770
A807	6.50H	16PR	128/124	K	13.0	853	230	1800/1600	770
A808	6.50H	16PR	128/124	K	16.5	855	235	1800/1600	770
A812	6.50H	16PR	128/124	K	15.0	855	230	1800/1600	770
A833	6.50H	16PR	128/124	L	15.0	855	235	1800/1600	770

9.00R16



A879

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A879	6.50H	8PR	126/124	K	15.9	916	250	1700/1600	450

255/100R16LT



A879

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A879	6.50H	8PR	126/124	K	15.9	916	250	1700/1600	450

37×12.5R16.5LT



A889

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A889	8.25	10PR	134	N	14.1	928	318	2120	450

8R17.5



A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A852	6.00	12PR	121/120	M	11.5	784	208	1450/1400	625

8.5R17.5



A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A852	6.00	12PR	121/120	M	11.5	784	208	1450/1400	625

9.5R17.5



A851



A837



A838



A829

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A851	6.75	18PR	143/141	J	13.6	842	240	2725/2575	875
A837	6.75	18PR	143/141	J	14.5	842	240	2725/2575	875
A838	6.75	18PR	143/141	J	15.5	842	240	2725/2575	875
A829	6.75	18PR	143/141	J	15.9	842	240	2725/2575	875

10R17.5



A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A852	7.5	16PR	143/141	J	13.0	858	254	2725/2527	850

205/75R17.5



A863

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A863	6.00	16PR	124/122	M	12.1	753	205	1600/1500	750

215/75R17.5



A852



A855



A863

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A852	6.00	18PR	135/133	J	13.0	767	212	2180/2060	860
A855	6.00	16PR	135/133	J	13.6	767	212	2180/2060	865
A863	6.00	16PR	135/133	K	12.1	767	212	2180/2060	865

215/70R17.5



A890



A890PLUS

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A890	6.00G	10PR	118/116	L	11.5	747	211	1320/1250	590
A890 PLUS	6.00G	10PR	118/116	L	12	747	211	1320/1250	590

225/80R17.5



A510

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A510	6.75	16PR	123/122	L	15.6	811	226	1550/1500	700

235/75R17.5



A852



A855



A863



A809

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A852	6.75	18PR	143/141	J	13.0	797	233	2725/2575	860
A855	6.75	18PR	143/141	J	13.6	797	233	2725/2575	865
A863	6.75	18PR	143/141	K	12.1	797	233	2725/2575	865
A809	6.75	18PR	143/141	G	18.0	797	233	2725/2575	900

245/70R17.5



A881

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A881	7.50	18PR	143/141	J	13.6	789	248	2725/2575	875

225/70R19.5



A851



A855

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A851	6.75	14PR	128/126	M	13.0	811	226	1800/1700	760
A855	6.75	14PR	128/126	L	15.0	817	226	1800/1700	760

245/70R19.5



A851



A855

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A851	7.50	16PR	135/133	L	13.0	839	248	2180/2060	830
A855	7.50	14PR	133/131	L	15.0	845	248	2060/1950	760

285/70R19.5



A837



A838

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A837	8.25	18PR	150/148	J	14.1	895	283	3350/3150	900
A838	8.25	18PR	150/148	J	16.5	895	283	3350/3150	900

265/70R19.5



A855



A863



A837



A838

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A855	7.50	16PR	140/138	M	17.5	867	262	2500/2360	830
	7.50	18PR	143/141	J	15.1	867	262	2725/2575	850
A863	7.50	18PR	140/138	M	12.6	867	262	2500/2360	775
A837	7.50	18PR	143/141	J	13.5	863	260	2725/2575	850
A838	7.50	18PR	143/141	J	15.5	867	260	2725/2575	850

435/50R19.5



A882

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A882	14.00	22PR	160	J	14.5	931	438	-	-

445/45R19.5



A882

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A882	15.00	22PR	160	J	14.5	895	446	4500	900

10.00R20



A801G+



A801



A807



A808



A809



A812



AX831



AX808



AX833



AX935

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A801G+	7.50	18PR	149/146	K	16.5	1034	274	3250/3000	930
A801	7.50	18PR	149/146	K	16.5	1054	278	3250/3000	930
A807	7.50	18PR	149/146	K	16.0	1054	278	3250/3000	930
A808	7.50	18PR	149/146	K	18.5	1054	278	3250/3000	930
A809	7.50	18PR	149/146	G	18.0	1054	278	3250/3000	930
A812	7.50	18PR	149/146	K	18.5	1054	278	3250/3000	930
AX831	7.50	18PR	149/146	K	16.9	1054	278	3250/3000	930
AX808	7.50	18PR	149/146	J	17.9	1065	278	3250/3000	930
AX833	7.50	18PR	149/146	F	22.4	1065	278	3250/3000	930
AX935	7.50	18PR	149/146	K	17.5	1054	276	3250/3000	930

11.00R20



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A801	8.00	18PR	152/149	K	17.0	1085	293	3550/3250	930
A807	8.00	18PR	152/149	K	16.5	1085	293	3550/3250	930
A808	8.00	18PR	152/149	K	19.5	1085	293	3550/3250	930
A809	8.00	18PR	152/149	G	20.5	1085	293	3550/3250	930
A812	8.00	18PR	152/149	K	20.0	1085	293	3550/3250	930
A815	8.00	18PR	152/149	G	24.5	1085	293	3550/3250	930
A835	8.00	18PR	152/149	K	15.0	1076	286	3550/3250	930
AX831	8.00	18PR	152/149	K	16.9	1085	293	3550/3250	930
AX808	8.00	18PR	152/149	K	17.9	1085	293	3550/3250	930
AX833	8.00	18PR	152/149	F	24.7	1085	293	3550/3250	930

12.00R20



A801L



A803



A801



A801PLUS



A807



A808



A809



A811



A812



A815



A815 PLUS



A833



A817



A877



A899



AX831



AX808



AX833

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A801L	8.50	20PR	156/153	K	16.0	1125	309	4000/3650	900
A803	8.50	20PR	156/153	K	16.0	1106	309	4000/3650	900
A801	8.50	20PR	156/153	K	17.5	1125	313	4000/3650	900
A801 PLUS	8.50	22PR	158/155	J	17.5	1125	315	4250/3875	900
A807	8.50	20PR	156/153	K	17.0	1125	328	4000/3650	900
A808	8.50	20PR	156/153	K	20.5	1125	313	4000/3650	900
A809	8.50	20PR	156/153	G	22.5	1125	310	4000/3650	900
	8.50	22PR	158/155	G	22.5	1125	310	4250/3875	970
A811	8.50	20PR	156/153	G	22.5	1121	314	4000/3650	900
A812	8.50	20PR	156/153	J	21.0	1125	314	4000/3650	900
A815	8.50	20PR	156/153	G	24.5	1125	313	4000/3650	900
A815 PLUS	8.50	20PR	156/153	G	24.5	1125	313	4000/3650	900
A833	8.50	20PR	156/153	G	22.0	1132	310	4000/3650	900
A817	8.50	20PR	156/153	G	22.5	1120	303	4000/3650	900
A877	8.50	20PR	156/153	G	19.0	1120.8	313	4000/3650	900
A899	8.50	22PR	158/155	F	26.0	1125	315	4250/3875	830
AX831	8.50	20PR	156/153	K	16.9	1125	315	4000/3650	900
AX808	8.50	20PR	156/153	J	17.9	1136	315	4000/3650	900
AX833	8.50	20PR	156/153	F	24.7	1136	315	4000/3650	900

8.25R20



A801



A812

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A801	6.50	16PR	139/137	K	15.3	974	236	2430/2300	900
A812	6.50H	16PR	139/137	K	16.5	974	236	2430/2300	930

9.00R20



A801



A807



A808



A812

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A801	7.00	16PR	144/142	K	15.5	1019	259	2800/2650	900
A807	7.00	16PR	144/142	K	15.5	1004	260	2800/2650	900
A808	7.00	16PR	144/142	K	16.5	1019	259	2800/2650	900
A812	7.00	16PR	144/142	K	17.5	1019	259	2800/2650	900

7.50R20



A502

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A502	6.00	16PR	133/131	M	14.1	935	215	2060/1950	930

12.5R20



A891

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A891	11.00	18PR	145	L	16.9	1120	350	3250	650

14.00R20



A857



A859

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A857	10.00	20PR	164/161	J	20.0	1253	375	5000/4625	790
A859	10.00	20PR	164/161	J	20.0	1253	375	5000/4625	790

16.00R20



A859

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A859	11.25	22PR	174/171	G	20.5	1309	438	6700/6150	760

395/85R20



A859

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A859	10.00	14PR	158	J	25	1180	396	4250	660

335/80R20MPT



A879

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A879	11.00	18PR	149	K	16.9	1044	340	3250	650

425/85R21



A875

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A875	10.00	24PR	167	D	24	1260	425	6100	550

365/80R20



A859

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A859	10.00	16PR	160	K	20	1092	364	4500	900

11R22.5



A854



A863A



A801A



A803



A511



A512



A878



A825



A822



A824



A801



A802



A809



A810



A816



A832



A821+



A850



A826

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A854	8.25	18PR	151/148	G	19.0	1054	279	3450/3150	930
A863A	8.25	18PR	149/146	K	20.0	1051	279	3250/3000	930
A801A	8.25	18PR	149/146	L	14.5	1051	279	3250/3000	930
A803	8.25	18PR	151/148	K	17.0	1054	292	3450/3150	930
	8.25	20PR	152/149	M	17.0	1054	292	3550/3250	930
A511	8.25	18PR	146/143	M	14.1	1054	279	3450/3150	930
A512	8.25	18PR	151/148	K	19.4	1065	279	3450/3150	930
A878	8.25	18PR	151/148	L	14.5	1040	279	3250/3000	930
A825	8.25	16PR	146/143	M	15.5	1054	282	3000/2725	830
A822	8.25	16PR	146/143	M	10.5	1054	282	3000/2725	830
A824	8.25	16PR	146/143	M	10.5	1054	282	3000/2725	830
A801	8.25	18PR	151/148	K	14.5	1054	292	3450/3150	930
A802	8.25	18PR	151/148	K	18.5	1054	292	3450/3150	930
A809	8.25	18PR	151/148	G	20.5	1054	279	3450/3150	930
A810	8.25	18PR	151/148	G	20.5	1054	292	3450/3150	930
A816	8.25	18PR	151/148	K	17.0	1054	292	3450/3150	930
A832	8.25	18PR	151/148	K	19.5	1054	292	3450/3150	930
A821+	8.25	18PR	151/148	K	17.0	1054	292	3450/3150	930
A850	8.25	18PR	151/148	K	18.0	1052	279	3450/3150	930
A826	8.25	16PR	146/143	L	20.5	1054	282	3000/2725	830

12R22.5



A854



A803



A801



A802



A809



A812



A816



A832



A821+



A850

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A854	9.00	18PR	152/149	G	19.0	1085	290	3350/3250	930
A803	9.00	18PR	152/149	K	17.0	1085	296	3550/3250	930
A801	9.00	18PR	152/149	K	14.5	1085	300	3550/3250	930
A802	9.00	18PR	152/149	K	18.5	1082	300	3550/3250	930
A809	9.00	18PR	152/149	G	20.5	1085	300	3550/3250	930
A812	9.00	18PR	152/149	K	22.0	1085	300	3550/3250	930
A816	9.00	18PR	152/149	K	16.5	1085	300	3550/3250	930
A832	9.00	18PR	152/149	K	20.5	1085	300	3550/3250	930
A821+	9.00	18PR	152/149	K	17.0	1085	300	3550/3250	930
A850	9.00	18PR	152/149	K	18.0	1085	300	3550/3250	930

13R22.5



A803



A801



A802



A809



A816



A832



A869



A850

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A803	9.75	18PR	154/151	K	18.5	1124	331	3750/3450	830
A801	9.75	18PR	154/151	K	15.0	1124	331	3750/3450	830
A802	9.75	18PR	154/151	K	19.5	1124	331	3750/3450	830
A809	9.75	18PR	154/151	G	20.5	1124	331	3750/3450	830
A816	9.75	18PR	154/151	K	18.0	1124	331	3750/3450	830
A832	9.75	18PR	154/151	K	19.5	1124	331	3750/3450	830
A869	9.75	20PR	154/151	K	17.0	1115	320	3750/3450	830
A850	9.75	18PR	154/151	K	18.5	1124	331	3750/3450	830

9R22.5



A858

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A858	6.75	14PR	136/134	L	14.5	974	229	2240/2120	760

10R22.5



A851



A858

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A851	7.50	16PR	144/142	L	15.1	1019	254	2800/2650	900
A858	7.50	16PR	144/142	M	15.0	1019	254	2800/2650	790

255/70R22.5



A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A852	7.50	16PR	140/137	N	10.5	930	255	2500/2300	830

275/70R22.5



A852



A853



A809



A832

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A852	8.25	16PR	148/145	M	14.5	958	274	3150/2900	900
A853	8.25	16PR	148/145	K	20.5	958	274	3150/2900	900
A809	8.25	16PR	148/145	G	20.5	958	274	3150/2900	900
A832	8.25	16PR	148/145	M	20.5	958	274	3150/2900	900

275/80R22.5



A855



A506

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A855	8.25	18PR	149/146	M	17.4	1018	276	3250/3000	900
A506	8.25	18PR	149/146	M	14.6	1012	276	3250/3000	900

295/60R22.5



A851



A853

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A851	9.00	18PR	150/147	K	16.0	926	292	3350/3075	900
A853	9.00	18PR	150/147	K	19.0	926	292	3350/3075	900

295/75R22.5



A885



A825



A822



A826

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A885	9.00	14PR	144/141	L	24	1020	297	2800/2527	760
A825	9.00	16PR	146/143	M	15.5	1014	300	3000/2725	830
A822	9.00	16PR	146/143	M	10.5	1014	300	3000/2725	830
A826	9.00	16PR	146/143	L	20.5	1014	300	3000/2725	830

295/80R22.5



A854



A861



A803



A878



A801



A802



A809



A832



A821+



AX865



AX510

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A854	9.00	18PR	152/149	G	19.0	1044	312	3550/3250	900
A861	9.00	18PR	152/149	M	15.0	1044	298	3550/3250	900
A803	9.00	18PR	152/149	K	17.0	1044	312	3550/3250	900
A878	9.00	18PR	152/149	L	14.5	1032	298	3550/3250	900
A801	9.00	18PR	152/149	K	15.5	1044	312	3550/3250	900
A802	9.00	18PR	152/149	K	18.5	1044	312	3550/3250	900
A809	9.00	18PR	152/149	G	20.5	1044	312	3550/3250	900
A832	9.00	18PR	152/149	K	19.5	1044	312	3550/3250	900
A821+	9.00	18PR	152/149	K	17.0	1044	312	3550/3250	900
AX865	9.00	18PR	152/149	L	20.4	1050	298	3550/3250	900
AX510	9.00	20PR	154/149	L	16.4	1044	298	3750/3250	850

315/80R22.5



A853



A854



A854 PLUS



A869A



A872



A880



A801



A801A



A801G+



A803



A701



A878



A802



A823



A809



A813



A832

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A853	9.00	20PR	157/154	L	20.5	1076	312	4125/3750	900
A854	9.00	20PR	157/154	J	19.0	1076	308	4125/3750	900
A854 PLUS	9.00	22PR	167/164	J	24.5	1076	312	5450/5000	900
A880	9.00	20PR	157/154	L	16.5	1076	312	4125/3750	900
A801	9.00	20PR	157/154	K	17.0	1076	308	4125/3750	830
A801A	9.00	20PR	157/154	K	15.0	1068	312	4125/3750	830
A801G+	9.00	20PR	157/154	K	14.5	1076	308	4125/3750	830
A803	9.00	20PR	157/154	K	17.0	1076	308	4125/3750	900
A701	9.00	20PR	157/154	K	14.5	1076	312	4125/3750	830
A878	9.00	20PR	157/154	L	14.5	1068	312	4125/3750	900
A802	9.00	20PR	157/154	K	18.5	1076	308	4125/3750	900
A823	9.00	20PR	157/154	K	14.5	1076	308	4125/3750	830
A809	9.00	20PR	157/154	G	20.5	1076	308	4125/3750	900
	9.00	22PR	167/164	D	22.0	1083	308	5450/5000	900
A813	9.00	20PR	157/154	K	17.5	1076	308	4125/3750	830
A832	9.00	20PR	157/154	K	19.5	1076	308	4125/3750	900
A869A	9.00	20PR	157/154	K	14.5	1068	312	4125/3750	900
A872	9.00	20PR	157/154	K	14.0	1076	312	4125/3750	900

315/60R22.5



A851



A865



A802

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A851	9.75	20PR	153/150	K	14.5	950	313	3650/3350	900
A865	9.75	20PR	153/150	K	22.0	950	313	3550/3250	900
A802	9.75	18PR	152/148	L	17.9	950	313	3550/3150	900

385/55R22.5



A864

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A864	12.25	20PR	160	K	15.5	996	386	4500	900

315/70R22.5



A851



A853

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A851	9.00	18PR	151/148	M	14.5	1014	312	3450/3150	830
A853	9.00	18PR	151/148	M	19.0	1014	312	3450/3150	830

385/65R22.5



A806



A861



A861 PLUS



A836



A507



A805

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A806	11.75	20PR	160	K	16.0	1072	392	4500	900
A861	11.75	20PR	160	K	15.5	1072	390	4500	900
A861 PLUS	11.75	24PR	164	K	16.5	1072	390	5000	900
A836	11.75	20PR	160	K	16.5	1072	390	4500	900
A507	11.75	24PR	164	J	17.4	1072	389	5000	930
A805	11.75	20PR	160	K	16.0	1072	390	4500	900

425/65R22.5



A856



A503

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A856	13.00	20PR	165	K	17.5	1124	420	5150	830
A503	13.00	20PR	165	J	15.9	1124	430	5150	825

445/50R22.5



A882

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A882	14.00	20PR	161	J	13.5	1018	445	-	-

445/65R22.5



A856

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A856	13.00	20PR	168	L	17.5	1150	444	5600	830

12.00R24



A801C



A801



A807



A829



A817



A582



A814

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A801C	8.50	20PR	160/157	K	15.5	1226	306	4500/4125	900
A801	8.50	20PR	160/157	K	17.5	1226	312	4500/4125	900
A807	8.50	20PR	160/157	K	15.5	1208	306	4500/4125	900
A829	8.50	20PR	160/157	K	18.0	1213	306	4500/4125	900
A817	8.50	20PR	160/157	K	20.0	1224	310	4500/4125	900
A582	8.50	20PR	160/157	K	18.0	1226	315	4500/4125	900
A814	8.50	24PR	164/161	F	32	1226	315	5000	850

325/95R24



A831



A505

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A831	9.00	20PR	162/160	K	15.6	1226	325	4750/4500	850
A505	9.00	22PR	162/160	K	15.9	1228	325	4750/4500	850

285/75R24.5



A825



A822



A826

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A825	8.25	16PR	147/144	M	15.5	1050	285	3075/2800	830
A822	8.25	16PR	147/144	M	10.5	1050	285	3075/2800	830
A826	8.25	16PR	147/144	L	20.5	1050	285	3075/2800	830

11R24.5



A822



A825



A809



A826

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpg)
A825	8.25	16PR	149/146	M	15.5	1104	284	3250/3000	830
A822	8.25	16PR	149/146	M	10.5	1104	284	3250/3000	830
A809	8.25	16PR	149/146	G	20.5	1104	276	3250/3000	830
A826	8.25	16PR	149/146	L	20.5	1104	284	3250/3000	830