Ver 26.10



SPORTRAK TIRE

just run just win

TRUCK / BUS TIRES



ENTERPRISE INTRODUCTION

Sportrak Tire Co., Ltd. has accumulated more than two decades of solid expertise within the rubber tire industry, strategically positioning itself to engage in the end-to-end industrial chain operation of proprietary branded tires.We have forged a seamless full-spectrum supply chain layout, encompassing upstream import of natural rubber, trading of raw materials and auxiliary supplies, tire research & development, customized OEM production, global merchandising, as well as integrated logistics allocation and distribution services.Our diversified product spectrum comprises truck & bus tyres, passenger vehicle tyres, multiple-purpose special tyres, OTR tyres, motorcycle tyres and supporting automotive ancillary components.We adopt multifaceted trade modalities ranging from imported material processing and conventional general trade to 9710 cross-border e-commerce. Dedicated to diversified industrial layout, we aspire to evolve into a leading all-in-one comprehensive service provider across the global tire marketplace.

Against the volatile tides of the global economic landscape, our proprietary brand SPORTRAK persists in brand-oriented strategic operation, enforces stringent quality supervision over all products, and perpetually elevates core competitive strengths.Upholding the core tenet of "Integrity Rooted, Win-win Collaboration", we devote ourselves to establishing a borderless global supply chain ecosystem.In response to personalized market demands from overseas clients, we tailor-develop products adaptable to local consumption markets, deploy dedicated moulds to launch large-scale streamlined production so as to slash operational manufacturing costs. Subsequently, we conduct centralized packaging, sorting and classified distribution, so as to fully cater to diversified procurement demands of global buyers. To this day, we have delivered exceptional commercial value to business partners spanning over a hundred nations worldwide.

Our proprietary brand SPORTRAK has obtained the Trademark Registration Certificate (No. 14413527) issued by the Trademark Office of the State Administration for Industry and Commerce of China.Additionally, our products have successfully secured a full range of authoritative international certifications, including US DOT & SMARTWAY, European E-Mark, Gulf GCC, Saudi SASO, Mexican NOM, Brazilian INMETRO, Indonesian SNI and South American LATU certifications.Centering on the flagship brand SPORTRAK, we actively expand global markets and have built a comprehensive product matrix covering diverse specifications ranging from cost-effective models to high-performance variants.We boast a complete lineup of all-steel tires. In particular, our multiple-purpose special tyres have repeatedly been shortlisted for government bidding projects in Central Asia, the Middle East and multiple African nations.

Endowed with profound industry heritage and extensive global business networks, our brand SPORTRAK has established solid and stable sales channels across the globe. Our products are widely accessible in over a hundred countries, spanning Southeast Asia, Europe, North America, as well as emerging markets in the Middle East and Africa.Looking ahead, we will further deepen our global strategic layout, continuously broaden business scope and elevate service standards. We aim to forge a closer, more efficient and sustainably vibrant trade ecosystem, strive to emerge as a pacesetter within the global tire trade sector, and contribute greater momentum to the prosperity and advancement of international trade.

20+
More than 20 years tires experience

100+
More than 100 countries and regions

550+
More than 550 tire sizes

5000000+
More than 5 million tires exported annually

SINCERELY HOPE TO ESTABLISH A LONG-TERM AND
MUTUALLY BENEFICIAL COOPERATIVE RELATIONSHIP WITH YOU


SP301


SP302


SP303


SP304


SP304 PLUS


SP309


SP310


SP314


SP315


SPX315


SP322 PLUS


SP323 PLUS


SP328


SP328L/C/G+


SP329


SP396


SP396 PLUS


SP397


SP398


SP399


SP507


SPX509


SP510


SPX510


SP512


SP831


SP832


SP901


SP901 PLUS


SP902


SP908


SP909


SP909 PLUS


SP910


SP911


SP918


SP919


SP920


SP921+


SP923

SP305

SP306

SP307

SP307 PLUS

SP308

SP316

SP317

SP317 PLUS

SP319

SP321

SP339

SP359

SP366

SP393

SP395

SPX501

SP502

SP503

SP505

SP506

SP513

SP516

SP601

SP605

SP639

SP903

SP905

SP906

SP907

SP907 PLUS

SP912

SP913

SP915

SP915 PLUS

SP917

SP925

SP926

SP928

SP929

SP932

















































TBR ----Table of Contents

7.50R15LT 07
6.50R16LT 07
7.00R16LT 08
7.50R16LT 09
8.25R16LT 11
9.00R16 12
255/100R16LT 12
37×12.5R16.5LT 12
8R17.5 13
8.5R17.5 13
9.5R17.5 14
10R17.5 14
205/75R17.5 15
215/70R17.5 15
215/75R17.5 16
225/80R17.5 15
235/75R17.5 17
245/70R17.5 18
225/70R19.5 18
245/70R19.5 19
265/70R19.5 19
285/70R19.5 20
435/50R19.5 20
445/45R19.5 20
7.50R20 22
8.25R20 22
9.00R20 23
10.00R20 24
11.00R20 25
12.00R20 27
12.5R20 29
14.00R20 29
15.5R20 30
16.00R20 30
335/80R20MPT 30
365/80R20 31
395/85R20 31
425/85R21 31
9R22.5 32
10R22.5 32
11R22.5 33
12R22.5 35
13R22.5 37
255/70R22.5 32
275/70R22.5 39
275/80R22.5 39
295/60R22.5 40
295/75R22.5 40
295/80R22.5 41
315/60R22.5 45
315/70R22.5 45
315/80R22.5 43
385/55R22.5 45
385/65R22.5 46
425/65R22.5 47
445/50R22.5 47
445/65R22.5 47
12.00R24 49
325/95R24 48
11R24.5 51
285/75R24.5 52

7.50R15LT



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP328	6.00G	14PR	121/117	L	13	774	215	1450/1285	760

6.50R16LT







PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP310	5.5F	12PR	110/105	M	9.5	750	185	1060/925	670
SP328	5.5F	12PR	110/105	L	9.5	750	185	1060/925	670
SP366	5.5F	10PR	107/102	L	11	750	185	975/850	560

7.00R16LT











PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP310	5.5F	14PR	118/114	M	11.0	775	200	1320/1180	770
SP328	5.5F	14PR	118/114	L	11.0	775	200	1320/1180	770
SP366	5.5F	12PR	115/110	N	10.0	775	200	1215/1060	670
SP957	5.5F	14PR	118/114	L	10.5	775	200	1320/1180	770
SP962	5.5F	14PR	118/114	L	16.0	775	196	1320/1180	770

7.50R16LT


SP307


SP307 PLUS


SP328


SP366


SP502


SP901


SP908


SP912


SP918


SP935

7.50R16LT

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP307	6.00G	8PR	112/107	M	10.5	805	215	1120/975	460
SP307PLUS	6.00G	14PR	122/118	M	15.0	805	215	1500/1320	770
SP328	6.00G	16PR	125/121	M	10.0	805	215	1650/1450	870
SP366	6.00G	14PR	122/120	L	10.0	805	215	1500/1320	770
SP502	6.00G	16PR	125/121	M	10.0	805	215	1650/1450	870
SP901	6.00G	14PR	122/118	L	12.0	805	210	1500/1320	770
SP908	6.00G	14PR	122/118	L	14.6	805	215	1500/1320	770
SP912	6.00G	14PR	122/118	L	14.5	805	210	1500/1320	770
SP918	6.00G	16PR	125/121	L	20.0	815	215	1650/1450	870
SP935	6.00G	16PR	125/121	L	12.5	805	215	1650/1450	870

8.25R16LT


SP901


SP907


SP908


SP912


SP918


SP935


SP961

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP901	6.50H	16PR	128/124	L	13.0	855	230	1800/1600	770
SP907	6.50H	16PR	128/124	L	13.0	853	230	1800/1600	770
SP908	6.50H	16PR	128/124	K	16.0	855	235	1800/1600	770
SP912	6.50H	16PR	128/124	L	15.0	855	230	1800/1600	770
SP918	6.50H	16PR	128/124	L	21.0	855	235	1800/1600	770
SP935	6.50H	16PR	128/124	L	15.5	855	235	1800/1600	770
SP961	6.50H	16PR	128/124	J	18.0	855	235	1800/1600	770

9.00R16


SP329

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP329	6.50H	8PR	126/124	K	15.9	916	250	1700/1600	450

255/100R16LT


SP329

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP329	6.50H	8PR	126/124	K	15.9	916	250	1700/1600	450

37×12.5R16.5LT


SP339

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP339	8.25	10PR	134	N	14.1	928	318	2120	450

8R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP302	6.00	12PR	122/120	J	13	784	208	1500/1400	760

8.5R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP302	6.00	12PR	122/120	M	13	802	215	1500/1400	660

9.5R17.5









PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP301	6.75	18PR	143/141	J	13.6	842	240	2725/2575	875
SP928	6.75	18PR	143/141	J	14.5	842	240	2725/2575	875
SP929	6.75	18PR	143/141	J	16.0	842	240	2725/2575	875
SP962	6.75	18PR	143/141	J	15.9	842	240	2725/2575	875

10R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP302	7.5	16PR	143/141	J	13.0	858	254	2725/2527	850

205/75R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP516	6.00	16PR	124/122	M	12.1	753	205	1600/1500	750

215/70R17.5





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP317	6.00G	10PR	118/116	L	11.5	747	211	1320/1250	590
SP317 PLUS	6.00G	10PR	118/116	L	12	747	211	1320/1250	590

225/80R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP510	6.75	16PR	123/122	L	15.6	811	226	1550/1500	700

215/75R17.5











PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP302	6.00	18PR	135/133	J	13.0	767	212	2180/2060	900
SP305	6.00	18PR	135/133	J	13.6	767	212	2180/2060	865
SP516	6.00	18PR	135/133	K	12.1	767	212	2180/2060	865
SP925	6.00	18PR	135/133	J	13.5	767	215	2180/2060	850
SP926	6.00	18PR	135/133	J	15.5	767	215	2180/2060	850

235/75R17.5


SP302


SP305


SP516


SP909


SP925


SP926

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP302	6.75	18PR	143/141	J	13.0	797	233	2725/2527	900
SP305	6.75	18PR	143/141	J	13.6	797	233	2725/2575	865
SP516	6.75	18PR	143/141	K	12.1	797	233	2725/2575	865
SP909	6.75	18PR	143/141	G	18.0	797	233	2725/2575	900
SP925	6.75	18PR	143/141	J	13.5	797	238	2725/2575	875
SP926	6.75	18PR	143/141	J	15.5	797	238	2725/2575	875

245/70R17.5


SP513

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP513	7.50	18PR	143/141	J	13.6	789	248	2725/2575	875

225/70R19.5


SP301


SP305

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP301	6.75	14PR	128/126	M	13.0	811	226	1800/1700	760
SP305	6.75	14PR	128/126	L	15.0	817	226	1800/1700	760

245/70R19.5


SP301


SP305

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP301	7.50	16PR	135/133	L	13.0	839	248	2180/2060	830
SP305	7.50	14PR	133/131	L	15.0	845	248	2060/1950	760

265/70R19.5


SP305


SP516


SP928


SP929

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP305	7.50	18PR	143/141	J	15.1	867	262	2727/2575	850
SP516	7.50	18PR	140/138	M	12.6	867	262	2500/2360	775
SP928	7.50	18PR	143/141	J	13.5	863	260	2727/2575	850
SP929	7.50	18PR	143/141	J	15.5	867	260	2727/2575	850

285/70R19.5


SP928


SP929

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP928	8.25	18PR	150/148	J	14.1	895	283	3350/3150	900
SP929	8.25	18PR	150/148	J	16.5	895	283	3350/3150	900

435/50R19.5


SP399


SP919

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP399	14.00	20PR	164	J	13.0	931	438	5000	900
SP919	14.00	20PR	164	J	13.0	931	438	5000	900

445/45R19.5


SP399


SP919

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP399	15.00	22PR	160	J	14.5	895	446	4500	900
SP919	15.00	20PR	160	J	13.0	895	446	4500	900



7.50R20



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP502	6.00	16PR	133/131	M	14.1	935	215	2060/1950	930

8.25R20







PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP901	6.50	16PR	139/137	K	15.0	974	236	2430/2300	930
SP908	6.50	16PR	139/137	K	15.9	974	236	2430/2300	930
SP912	6.50	16PR	139/137	K	16.5	974	236	2430/2300	930

9.00R20











PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP901	7.00	16PR	144/142	K	15.5	1019	259	2800/2650	900
SP907	7.00	16PR	144/142	K	18.5	1004	260	2800/2650	900
SP912	7.00	16PR	144/142	K	17.5	1019	259	2800/2650	900
SP961	7.00	16PR	144/142	J	19.5	1019	259	2800/2650	900
SP935	7.00	18PR	145/143	K	17.0	1019	259	2900/2725	930

10.00R20



















PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP901	7.50	18PR	149/146	K	16.5	1054	278	3250/3000	930
SP908	7.50	18PR	149/146	K	18.5	1054	278	3250/3000	930
SP909	7.50	18PR	149/146	G	18.0	1054	278	3250/3000	930
SP912	7.50	18PR	149/146	K	18.5	1054	278	3250/3000	930
SP935	7.50	18PR	149/146	K	17.0	1054	278	3250/3000	930
SPX935	7.50	18PR	149/146	K	16.5	1054	276	3250/3000	930
SP951	7.50	18PR	149/146	G	22.0	1060	276	3250/3000	970
SP961	7.50	18PR	149/146	J	20.5	1054	278	3250/3000	930
SP963	7.50	18PR	149/146	K	18.0	1054	278	3250/3000	930

11.00R20


SP901


SP907


SP908


SP909


SP912


SP915


SP923


SP935


SP950


SP951


SP963


SP992


SP999

11.00R20

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP901	8.00	18PR	152/149	K	17.0	1085	293	3550/3250	930
SP907	8.00	18PR	152/149	K	16.5	1085	293	3550/3250	930
SP908	8.00	18PR	152/149	K	21.5	1085	293	3550/3250	930
SP909	8.00	18PR	152/149	G	20.5	1085	293	3550/3250	930
SP912	8.00	18PR	152/149	K	20.0	1085	293	3550/3250	930
SP915	8.00	18PR	152/149	G	24.5	1085	293	3550/3250	930
SP923	8.00	18PR	152/149	K	15.0	1076	286	3550/3250	930
SP935	8.00	18PR	152/149	K	17.0	1085	293	3550/3250	930
SP950	8.00	18PR	152/149	K	18.0	1085	293	3550/3250	930
SP951	8.00	18PR	152/149	F	24.0	1085	293	3550/3250	930
SP963	8.00	18PR	152/149	K	18.0	1085	293	3550/3250	930
SP992	8.00	18PR	152/149	K	19.0	1085	293	3550/3250	930
SP999	8.00	18PR	152/149	F	24.0	1085	293	3550/3250	930

12.00R20





































PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP328L	8.50	20PR	156/153	K	16.0	1125	309	4000/3650	900
SP398	8.50	20PR	156/153	K	16.0	1106	309	4000/3650	900
SPX509	8.50	20PR	156/153	F	24.7	1136	315	4000/3650	900
SP901	8.50	20PR	156/153	K	17.5	1125	313	4000/3650	900
SP901 PLUS	8.50	22PR	156/153	J	17.5	1125	315	4000/3650	900
SP907	8.50	20PR	156/153	K	17.0	1125	328	4000/3650	900
SP909	8.50	20PR	156/153	G	22.5	1125	310	4000/3650	900
	8.50	22PR	158/155	G	22.5	1125	310	4250/3875	970
SP911	8.50	20PR	156/153	K	19.5	1121	314	4000/3650	900
SP912	8.50	20PR	156/153	J	21.0	1125	314	4000/3650	900
SP915	8.50	20PR	156/153	G	24.5	1125	313	4000/3650	900
SP915 PLUS	8.50	20PR	156/153	F	24.5	1125	313	4000/3650	900
SP918	8.50	20PR	156/153	G	22.0	1132	310	4000/3650	900
SP935PLUS	8.50	22PR	158/155	K	18.0	1125	315	4250/3875	970
SP950	8.50	22PR	158/155	K	18.0	1125	315	4250/3875	970
SP951	8.50	20PR	156/153	F	24.5	1125	315	4000/3650	900
SP966	8.50	22PR	158/155	K	20.0	1125	315	4250/3875	970
SP981	8.50	20PR	156/153	G	22.5	1120	303	4000/3650	900
SP999	8.50	22PR	158/155	F	26.0	1125	315	4250/3875	970

12.5R20



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP319	9.00	18PR	149	L	21.4	1120	350	3250	650

14.00R20







PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP307	10.00	18PR	161/158	K	20.0	1253	375	4625/4250	690
SP309	10.00	20PR	164/161	J	20.0	1253	375	5000/4625	790
SP321	10.00	20PR	164/161	J	20.0	1253	375	5000/4625	790

15.5R20





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP319	11.25	24PR	173	G	20.0	1265	440	6500	830
SP339	11.25	24PR	173	L	15.5	1260	440	6500	830

16.00R20



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP309	11.25	22PR	174/171	G	20.5	1309	438	6700/6150	760

335/80R20MPT





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP309	10.00	16PR	152	K	18.0	1044	340	3550	760
SP329	11.00	18PR	149	K	16.9	1044	340	3250	650

365/80R20



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP309	10.00	16PR	160	K	20	1092	364	4500	900

9R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP308	6.75	14PR	136/134	L	14.5	974	229	2240/2120	830

395/85R20





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP309	10.00	14PR	158	J	25	1180	396	4250	660
SP339	10.00	14PR	158	M	19	1196	396	4250	660

10R22.5





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP301	7.50	16PR	144/142	L	15.1	1019	254	2800/2650	900
SP308	7.50	16PR	144/142	M	15.0	1019	254	2800/2650	790

425/85R21



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP359	12.2-21	18PR	167	D	25	1260	425	5450	650

255/70R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP302	7.50	16PR	140/137	N	10.5	930	255	2500/2300	830

11R22.5





































PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP304	8.25	18PR	151/148	G	20.4	1054	279	3450/3150	930
SP398	8.25	20PR	152/149	M	17.0	1054	292	3550/3250	930
SP512	8.25	18PR	151/148	K	19.4	1065	279	3450/3150	930
SP605	8.25	18PR	151/148	K	15.5	1054	279	3450/3150	930
SP639	8.25	16PR	146/143	M	15.5	1054	282	3000/2725	830
SP832	8.25	16PR	146/143	M	10.5	1054	282	3000/2725	830
SP901	8.25	18PR	151/148	K	14.5	1054	292	3450/3150	930
SP902	8.25	18PR	151/148	K	18.5	1054	292	3450/3150	930
SP909	8.25	18PR	151/148	G	20.5	1054	279	3450/3150	930
SP910	8.25	18PR	151/148	G	20.5	1054	292	3450/3150	930
SP917	8.25	18PR	151/148	K	19.5	1054	292	3450/3150	930
SP935	8.25	20PR	152/149	K	17.0	1054	279	3550/3250	930
SP940	8.25	20PR	152/149	K	20.0	1054	279	3550/3250	930
SP958	8.25	20PR	152/149	K	17.0	1054	279	3550/3250	930
SP965	8.25	18PR	151/148	K	18.0	1054	292	3450/3150	930
SP967	8.25	18PR	151/148	K	20.5	1054	279	3450/3150	930
SP997	8.25	16PR	146/143	L	20.5	1054	282	3000/2725	830
SP932	8.25	18PR	151/148	K	23.0	1054	279	3450/3150	930

12R22.5


SP304


SP398


SP605


SP901


SP907 PLUS


SP909


SP909 PLUS


SP917


SP920


SP935


SP951


SP956 PLUS


SP963


SP990 PLUS


SP992

12R22.5

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP304	9.00	18PR	152/149	G	18.5	1085	290	3350/3250	930
SP398	9.00	18PR	152/149	K	17.0	1085	296	3550/3250	930
SP605	9.00	18PR	152/149	L	17.0	1085	300	3550/3250	930
SP901	9.00	18PR	152/149	K	14.5	1085	300	3550/3250	930
SP907 PLUS	9.00	20PR	154/151	K	19.0	1085	300	3750/3450	970
SP909	9.00	18PR	152/149	G	20.5	1085	300	3550/3250	930
SP909 PLUS	9.00	18PR	152/149	F	25.0	1085	300	3550/3250	930
SP917	9.00	18PR	152/149	K	20.5	1085	300	3550/3250	930
SP920	9.00	20PR	154/151	K	20.0	1085	300	3750/3450	970
SP935	9.00	20PR	156/153	K	17.5	1085	315	4000/3650	900
SP951	9.00	20PR	154/151	F	25.0	1085	300	3750/3450	970
SP956 PLUS	9.00	20PR	154/151	L	17.0	1085	300	3750/3450	970
SP963	9.00	18PR	152/149	K	20.0	1085	300	3550/3250	930
SP990 PLUS	9.00	20PR	154/151	L	18.5	1085	300	3550/3250	970
SP992	9.00	18PR	152/149	K	20.0	1085	300	3550/3250	930

13R22.5


SP304


SP398


SP901


SP909


SP909 PLUS


SP917


SP935


SP935 PLUS


SP950


SP992


SP999


SP932

13R22.5

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP304	9.75	18PR	154/151	K	20.5	1124	309	3750/3450	830
SP398	9.75	18PR	154/151	K	18.5	1124	331	3750/3450	830
SP901	9.75	20PR	156/153	K	15.0	1124	331	3750/3450	830
SP909	9.75	20PR	156/153	G	20.5	1124	331	4000/3650	830
SP909 PLUS	9.75	22PR	158/156	G	20.5	1114	320	4250/4000	830
SP917	9.75	18PR	154/151	K	19.5	1124	331	3750/3450	830
SP935	9.75	20PR	156/153	K	17.0	1124	309	4000/3650	830
SP935 PLUS	9.75	22PR	158/156	K	17.0	1124	320	4250/4000	830
SP950	9.75	22PR	158/156	K	20.0	1124	320	4250/4000	830
SP992	9.75	22PR	158/156	K	20.0	1124	320	4250/4000	830
SP999	9.75	22PR	156/153	F	26.0	1132	320	4000/3650	930
SP932	9.75	18PR	154/151	K	18.0	1124	320	3750/3450	900

275/70R22.5









PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP302	8.25	16PR	148/145	M	13.0	958	276	3150/2900	900
SP303	8.25	16PR	148/145	K	20.5	958	274	3150/2900	900
SP909	8.25	16PR	148/145	G	20.5	958	274	3150/2900	900
SP917	8.25	16PR	148/145	M	20.5	958	274	3150/2900	900

275/80R22.5





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP305	8.25	18PR	149/146	M	17.4	1018	276	3250/3000	900
SP506	8.25	18PR	149/146	M	14.6	1012	276	3250/3000	900

295/60R22.5





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP301	9.00	18PR	150/147	K	16.0	926	292	3350/3075	900
SP303	9.00	18PR	150/147	K	19.0	926	292	3350/3075	900

295/75R22.5









PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP639	9.00	16PR	146/143	M	15.5	1014	300	3000/2725	830
SP831	9.00	16PR	146/143	M	10.5	1014	300	3000/2725	830
SP903	9.00	16PR	146/143	L	20.5	1014	298	3000/2725	830
SP997	9.00	16PR	146/143	L	20.5	1014	300	3000/2725	830

295/80R22.5

































PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP303	9.00	20PR	156/149	K	21.0	1044	298	4000/3250	850
SP304	9.00	18PR	152/149	G	19.0	1044	312	3550/3250	900
SPX315	9.00	20PR	154/149	L	20.4	1050	298	3750/3250	900
SP316	9.00	20PR	156/149	K	17.0	1044	298	4000/3250	850
SP322 PLUS	9.00	20PR	154/150	L	16.5	1044	298	3750/3350	850
SP323 PLUS	9.00	20PR	154/150	L	20.5	1050	298	3750/3350	850
SP398	9.00	18PR	152/149	K	17.0	1044	312	3550/3250	900
SPX510	9.00	20PR	154/149	L	16.4	1044	298	3750/3250	850
SP605	9.00	20PR	154/150	L	17.0	1043	300	3750/3350	850
SP901	9.00	18PR	152/149	K	15.5	1044	312	3550/3250	900
SP902	9.00	18PR	152/149	K	18.5	1044	312	3550/3250	900
SP909	9.00	18PR	152/149	G	20.5	1044	312	3550/3250	900
SP917	9.00	18PR	152/149	K	19.5	1044	312	3550/3250	900
SP921+	9.00	18PR	152/149	K	17.0	1044	312	3550/3250	900
SP935	9.00	20PR	154/150	L	17.0	1043	300	3750/3350	850
SP991	9.00	20PR	154/150	G	20.5	1050	300	3750/3350	850

315/80R22.5


SP303


SP304


SP304 PLUS


SP316


SP322 PLUS


SP323 PLUS


SP328


SP328G+


SP398


SP601


SP902


SP906


SP909


SP909 PLUS


SP913


SP917


SP935A


SP935 PLUS


SP938

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP303	9.00	20PR	157/154	L	20.5	1076	312	4125/3750	900
SP304	9.00	20PR	157/154	J	23.0	1076	308	4125/3750	900
SP304 PLUS	9.00	22PR	167/164	D	24.5	1076	312	5450/5000	900
SP316	9.00	20PR	157/154	L	16.5	1076	312	4125/3750	900
SP322PLUS	9.00	22PR	158/156	K	16.5	1076	312	4250/4000	900
SP323PLUS	9.00	22PR	158/156	K	20.5	1076	312	4250/4000	900
SP328	9.00	20PR	157/154	K	17.0	1076	308	4125/3750	830
SP328G+	9.00	20PR	157/154	K	15.0	1076	312	4125/3750	900
SP398	9.00	20PR	157/154	K	17.0	1076	308	4125/3750	900
SP601	9.00	20PR	157/154	K	15.0	1076	312	4125/3750	900
SP902	9.00	20PR	157/154	K	18.5	1076	308	4125/3750	900
SP906	9.00	20PR	157/154	K	14.5	1076	308	4125/3750	830
SP909	9.00	20PR	157/154	G	20.5	1076	308	4125/3750	900
SP909PLUS	9.00	22PR	158/156	G	21.0	1082	308	4250/4000	900
SP913	9.00	20PR	157/154	K	17.5	1076	308	4125/3750	830
SP917	9.00	20PR	157/154	K	19.5	1076	308	4125/3750	900
SP935A	9.00	20PR	157/154	K	14.5	1076	308	4125/3750	900
SP935 PLUS	9.00	22PR	158/156	K	17.0	1076	312	4250/4000	900
SP938	9.00	20PR	157/154	K	15.0	1076	312	4125/3750	900

315/60R22.5


SP301


SP902

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP301	9.75	20PR	153/150	K	14.5	950	313	3650/3350	900
SP902	9.75	18PR	152/148	L	17.9	950	313	3550/3150	900

315/70R22.5


SP301


SP303


SP319

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP301	9.00	20PR	156/150	L	14.5	1014	312	4000/3350	900
SP303	9.00	18PR	151/148	M	19.0	1014	312	3450/3150	830
SP319	9.00	20PR	154/151	K	17.5	1012	312	3750/3450	930

385/55R22.5


SP314

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP314	12.25	20PR	160	K	16	996	386	4500	900

385/65R22.5


SP306


SP393


SP395


SP396


SP396 PLUS


SP397


SP507


SP905

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP306	11.75	22PR	162	J	15.5	1072	389	4750	930
SP393	11.75	20PR	160	K	16.0	1066	389	4500	900
SP395	11.75	20PR	160	K	16.0	1072	392	4500	900
SP396	11.75	20PR	160	K	15.5	1072	390	4500	900
SP396 PLUS	11.75	24PR	164	K	16.5	1072	390	5000	900
SP397	11.75	20PR	160	K	16.5	1072	390	4500	900
SP507	11.75	24PR	164	J	17.4	1072	389	5000	930
SP905	11.75	20PR	160	K	15.3	1072	390	4500	900

425/65R22.5





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP306	12.25	20PR	165	K	17.5	1124	420	5150	830
SP503	12.25	20PR	165	J	15.9	1124	430	5150	825

445/50R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP399	14.00	20PR	161	L	13.5	1018	445	4625	830

445/65R22.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP306	13.00	22PR	170	J	17.5	1150	444	6000	900

325/95R24













PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP501	9.00	22PR	162/160	K	15.9	1226	325	4750/4500	830
SPX501	9.00	22PR	162/160	K	15.9	1226	325	4750/4500	830
SP505	9.00	22PR	162/160	K	15.6	1228	325	4750/4500	850
SP909	8.5	22PR	162/160	K	23.5	1232	314	4750/4500	850
SP909 PLUS	8.5	22PR	162/160	K	23.5	1232	314	4750/4500	850
SP992	8.5	22PR	162/160	K	20	1225	314	4750/4500	850

12.00R24


SP328C


SP901


SP907


SP909


SP909 PLUS


SP962


SP981


SP982


SP983


SP992

12.00R24

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP328C	8.50	20PR	160/157	K	15.5	1226	306	4500/4125	900
SP901	8.50	20PR	160/157	K	15.5	1226	312	4500/4125	900
SP907	8.50	20PR	160/157	K	15.5	1208	306	4500/4125	900
SP909	8.50	22PR	162/160	K	23.5	1232	314	4750/4500	850
SP909 PLUS	8.50	22PR	162/160	K	23.5	1232	314	4750/4500	850
SP962	8.50	20PR	160/157	K	18.0	1213	306	4500/4125	900
SP981	8.50	20PR	160/157	K	20.0	1224	310	4500/4125	900
SP982	8.50	20PR	160/157	K	18.0	1226	315	4500/4125	900
SP983	8.50	24PR	164/161	L	32.0	1226	315	5000/4625	900
SP992	8.50	22PR	162/160	K	20.0	1225	314	4750/4500	850

11R24.5











PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP639	8.25	16PR	149/146	M	15.5	1104	284	3250/3000	830
SP831	8.25	16PR	149/146	M	10.5	1104	284	3250/3000	830
SP903	8.25	16PR	149/146	L	20.5	1104	279	3250/3000	830
SP909	8.25	16PR	149/146	G	20.5	1104	276	3250/3000	830
SP997	8.25	16PR	149/146	L	20.5	1104	284	3250/3000	830

285/75R24.5









PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
SP639	8.25	16PR	147/144	M	15.5	1050	285	3075/2800	830
SP831	8.25	16PR	147/144	M	10.5	1050	285	3075/2800	830
SP903	8.25	16PR	147/144	L	24.5	1050	283	3075/2800	830
SP997	8.25	16PR	147/144	L	20.5	1050	285	3075/2800	830

POWER SHOCK

SPORTRAK
OFF-THE-ROAD TIRES

FEEL FREE TO CHOOSE

- Wide tread width improves mobility and offers a more comfortable ride
- Unique compound to improve overall treadwear and cost per hour
- Tough construction for enhanced impact resistance

OTR PATTERN

STRONG STYLE
DURABLE
OVERLOAD
RESISTANT


SP101


SP102


SP103


SP105


SP106


SP107

PATTERN	SIZE&PR	POSITION	PATTERN	SIZE&PR	POSITION
SP101	14.00-24-16PR	E3/L3	SP102	17.5-25-16PR	E3/L3
	16.00-24-20PR	E3/L3		20.5-25-20PR	E3/L3
	16/70-20-16PR	E3/L3		23.5-25-20PR	E3/L3
	13.00-25-24PR	E3/L3		26.5-25-28PR	E3/L3
	15.5-25-16PR	E3/L3	SP103	13.00-24-12PR	G2/L2
	16.00-25-28PR	E3/L3		14.00-24-16PR	G2/L2
	18.00-25-32PR	E3/L3		17.5-25-16PR	G2/L2
	17.5-25-16PR	E3/L3		20.5-25-20PR	G2/L2
	20.5-25-20PR	E3/L3		23.5-25-20PR	G2/L2
	23.5-25-20PR	E3/L3	SP105	17.5-25-16PR	L5
	26.5-25-28PR	E3/L3		20.5-25-20PR	L5
	29.5-25-28PR	E3/L3		23.5-25-20PR	L5
SP106	14.00-20-18PR	SAND TIRE		26.5-25-28PR	L5
SP107	14.00R25NHS			29.5-25-28PR	L5
	16.00R25NHS				