

SUPERWAY

TRUCK / BUS TIRES
PRODUCT CATALOGUE

VER 26.11

GOOD QUALITY
COST-EFFECTIVE



20+
More than 20 years tires experience

100+
More than 100 countries and regions

550+
More than 550 tire sizes

5000000+
More than 5 million tires exported annually

SINCERELY HOPE TO ESTABLISH A LONG-TERM AND
MUTUALLY BENEFICIAL COOPERATIVE RELATIONSHIP WITH YOU


A852


A854


AX865


A801


A801L/G/G+


A879


A861


A861 PLUS


A836


A803


A507


AX833


A510


AX510


A822


A824


A801 PLUS


A802


A808


A809


A809 PLUS


A810


A811


A833


A835


A855


A857


A896


A858


A889


A875


A866


A508


A806


AX831


A502


A503


A505


A506


A881

A863

A701

A827

A825

A843

A805

A823

A807

A807PLUS

A812

A813

A815

A815 PLUS

A832

A818

A819

A837

A838

A867

A869/A869A

A869 PLUS

A872

A844

A845

A873

A890 PLUS

A848

A829

A849

A850

A874

A884

A817

A582

A814

A831

A887

A877

A826

A999

TBR ----Table of Contents

7.50R15LT 06
6.50R16LT 06
7.00R16LT 06
7.50R16LT 07
8.25R16LT 08
9.00R16 09
255/100R16LT 09
37×12.5R16.5LT 09
8R17.5 10
8.5R17.5 10
9.5R17.5 11
10R17.5 11
205/75R17.5 11
215/75R17.5 12
225/80R17.5 12
235/75R17.5 13
245/70R17.5 13
225/70R19.5 14
245/70R19.5 14
265/70R19.5 15
285/70R19.5 15
7.50R20 16
8.25R20 16
9.00R20 17
10.00R20 18
11.00R20 19
12.00R20 21
14.00R20 23
15.5R20 23
335/80R20MPT 23
395/85R20 24
425/85R21 24
255/70R22.5 24
11R22.5 25
12R22.5 27
13R22.5 29
275/70R22.5 30
275/80R22.5 31
295/75R22.5 31
295/80R22.5 33
315/60R22.5 36
315/80R22.5 35
385/65R22.5 37
425/65R22.5 38
325/95R24 38
12.00R24 39
11R24.5 40
285/75R24.5 41

7.50R15LT



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801	6.00G	14PR	121/117	L	13	774	215	1450/1285	760

6.50R16LT





PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801	5.5F	12PR	110/105	L	9.5	750	185	1060/925	670
A866	5.5F	10PR	107/102	L	11	750	185	975/850	560

7.00R16LT







PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801	5.5F	14PR	118/114	L	11.0	775	200	1320/1180	770
A866	5.5F	12PR	115/110	N	10.0	775	200	1215/1060	670
A829	5.5F	14PR	118/114	L	16.0	775	196	1320/1180	770

7.50R16LT


A857


A801


A866


A502


A801


A808


A812


A833


A869

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A857	6.00G	8PR	112/107	M	10.5	805	215	1120/975	460
A801	6.00G	16PR	125/121	M	10.0	805	215	1650/1450	870
A866	6.00G	14PR	122/120	L	10.0	805	215	1500/1320	770
A502	6.00G	16PR	125/121	M	10.0	805	215	1650/1450	870
A801	6.00G	14PR	122/118	L	12.0	805	210	1500/1320	770
A808	6.00G	14PR	122/118	L	14.6	805	215	1500/1320	770
A812	6.00G	14PR	122/118	L	14.5	805	210	1500/1320	770
A833	6.00G	16PR	125/121	L	20.0	815	215	1650/1450	870
A869	6.00G	16PR	125/121	L	12.5	805	215	1650/1450	870

8.25R16LT


A801


A807


A808


A812


A833


A869


A848

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801	6.50H	16PR	128/124	L	13.0	855	230	1800/1600	770
A807	6.50H	16PR	128/124	L	13.0	853	230	1800/1600	770
A808	6.50H	16PR	128/124	K	16.0	855	235	1800/1600	770
A812	6.50H	16PR	128/124	L	15.0	855	230	1800/1600	770
A833	6.50H	16PR	128/124	L	21.0	855	235	1800/1600	770
A869	6.50H	16PR	128/124	L	15.5	855	235	1800/1600	770
A848	6.50H	16PR	128/124	J	18.0	855	235	1800/1600	770

9.00R16



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A879	6.50H	8PR	126/124	K	15.9	916	250	1700/1600	450

255/100R16LT



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A879	6.50H	8PR	126/124	K	15.9	916	250	1700/1600	450

37×12.5R16.5LT



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A889	8.25	10PR	134	N	14.1	928	318	2120	450

8R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A852	6.00	12PR	122/120	J	13	784	208	1500/1400	760

8.5R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A852	6.00	12PR	122/120	M	13	802	215	1500/1400	660

9.5R17.5







PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A837	6.75	18PR	143/141	J	14.5	842	240	2725/2575	875
A838	6.75	18PR	143/141	J	16.0	842	240	2725/2575	875
A829	6.75	18PR	143/141	J	15.9	842	240	2725/2575	875

10R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A852	7.5	16PR	143/141	J	13.0	858	254	2725/2527	850

205/75R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A863	6.00	16PR	124/122	M	12.1	753	205	1600/1500	750

215/75R17.5











PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A852	6.00	18PR	135/133	J	13.0	767	212	2180/2060	900
A855	6.00	18PR	135/133	J	13.6	767	212	2180/2060	865
A863	6.00	18PR	135/133	K	12.1	767	212	2180/2060	865
A818	6.00	18PR	135/133	J	13.5	767	215	2180/2060	850
A819	6.00	18PR	135/133	J	15.5	767	215	2180/2060	850

225/80R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A510	6.75	16PR	123/122	L	15.6	811	226	1550/1500	700

235/75R17.5













PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A852	6.75	18PR	143/141	J	13.0	797	233	2725/2527	900
A855	6.75	18PR	143/141	J	13.6	797	233	2725/2575	865
A863	6.75	18PR	143/141	K	12.1	797	233	2725/2575	865
A809	6.75	18PR	143/141	G	18.0	797	233	2725/2575	900
A818	6.75	18PR	143/141	J	13.5	797	238	2725/2575	875
A819	6.75	18PR	143/141	J	15.5	797	238	2725/2575	875

245/70R17.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A881	7.50	18PR	143/141	J	13.6	789	248	2725/2575	875

225/70R19.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A855	6.75	14PR	128/126	L	15.0	817	226	1800/1700	760

245/70R19.5



PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A855	7.50	14PR	133/131	L	15.0	845	248	2060/1950	760

265/70R19.5


A855


A863


A837


A838

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A855	7.50	18PR	143/141	J	15.1	867	262	2727/2575	850
A863	7.50	18PR	140/138	M	12.6	867	262	2500/2360	775
A837	7.50	18PR	143/141	J	13.5	863	260	2727/2575	850
A838	7.50	18PR	143/141	J	15.5	867	260	2727/2575	850

285/70R19.5


A837


A838

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A837	8.25	18PR	150/148	J	14.1	895	283	3350/3150	900
A838	8.25	18PR	150/148	J	16.5	895	283	3350/3150	900

7.50R20


A502

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A502	6.00	16PR	133/131	M	14.1	935	215	2060/1950	930

8.25R20


A801


A808


A812

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801	6.50	16PR	139/137	K	15.0	974	236	2430/2300	930
A808	6.50	16PR	139/137	K	15.9	974	236	2430/2300	930
A812	6.50	16PR	139/137	K	16.5	974	236	2430/2300	930

9.00R20









PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801	7.00	16PR	144/142	K	15.5	1019	259	2800/2650	900
A812	7.00	16PR	144/142	K	17.5	1019	259	2800/2650	900
A848	7.00	16PR	144/142	J	19.5	1019	259	2800/2650	900
A869	7.00	18PR	145/143	K	17.0	1019	259	2900/2725	930

10.00R20



















PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801	7.50	18PR	149/146	K	16.5	1054	278	3250/3000	930
A808	7.50	18PR	149/146	K	18.5	1054	278	3250/3000	930
A809	7.50	18PR	149/146	G	18.0	1054	278	3250/3000	930
A812	7.50	18PR	149/146	K	18.5	1054	278	3250/3000	930
A869	7.50	18PR	149/146	K	17.0	1054	278	3250/3000	930
AX869	7.50	18PR	149/146	K	16.5	1054	276	3250/3000	930
A873	7.50	18PR	149/146	G	22.0	1060	276	3250/3000	970
A848	7.50	18PR	149/146	J	20.5	1054	278	3250/3000	930
A849	7.50	18PR	149/146	K	18.0	1054	278	3250/3000	930

11.00R20


A801


A807


A808


A809


A812


A815


A835


A869


A845


A873


A849


A877


A999

11.00R20

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801	8.00	18PR	152/149	K	17.0	1085	293	3550/3250	930
A807	8.00	18PR	152/149	K	16.5	1085	293	3550/3250	930
A808	8.00	18PR	152/149	K	21.5	1085	293	3550/3250	930
A809	8.00	18PR	152/149	G	20.5	1085	293	3550/3250	930
A812	8.00	18PR	152/149	K	20.0	1085	293	3550/3250	930
A815	8.00	18PR	152/149	G	24.5	1085	293	3550/3250	930
A835	8.00	18PR	152/149	K	15.0	1076	286	3550/3250	930
A869	8.00	18PR	152/149	K	17.0	1085	293	3550/3250	930
A845	8.00	18PR	152/149	K	18.0	1085	293	3550/3250	930
A873	8.00	18PR	152/149	F	24.0	1085	293	3550/3250	930
A849	8.00	18PR	152/149	K	18.0	1085	293	3550/3250	930
A877	8.00	18PR	152/149	K	19.0	1085	293	3550/3250	930
A999	8.00	18PR	152/149	F	24.0	1085	293	3550/3250	930

12.00R20


A801L


A803


AX833


A801


A801 PLUS


A807


A809


A811


A812


A815


A815 PLUS


A833


A869 PLUS


A845


A873


A874


A817


A999

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801L	8.50	20PR	156/153	K	16.0	1125	309	4000/3650	900
A803	8.50	20PR	156/153	K	16.0	1106	309	4000/3650	900
AX833	8.50	20PR	156/153	F	24.7	1136	315	4000/3650	900
A801	8.50	20PR	156/153	K	17.5	1125	313	4000/3650	900
A801 PLUS	8.50	22PR	156/153	J	17.5	1125	315	4000/3650	900
A807	8.50	20PR	156/153	K	17.0	1125	328	4000/3650	900
A809	8.50	20PR	156/153	G	22.5	1125	310	4000/3650	900
	8.50	22PR	158/155	G	22.5	1125	310	4250/3875	970
A811	8.50	20PR	156/153	K	19.5	1121	314	4000/3650	900
A812	8.50	20PR	156/153	J	21.0	1125	314	4000/3650	900
A815	8.50	20PR	156/153	G	24.5	1125	313	4000/3650	900
A815 PLUS	8.50	20PR	156/153	F	24.5	1125	313	4000/3650	900
A833	8.50	20PR	156/153	G	22.0	1132	310	4000/3650	900
A869 PLUS	8.50	22PR	158/155	K	18.0	1125	315	4250/3875	970
A845	8.50	22PR	158/155	K	18.0	1125	315	4250/3875	970
A873	8.50	20PR	156/153	F	24.5	1125	315	4000/3650	900
A874	8.50	22PR	158/155	K	20.0	1125	315	4250/3875	970
A817	8.50	20PR	156/153	G	22.5	1120	303	4000/3650	900
A999	8.50	22PR	158/155	F	26.0	1125	315	4250/3875	970

14.00R20


A857


A858

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A857	10.00	18PR	161/158	K	20.0	1253	375	4625/4250	690
A858	10.00	20PR	164/161	J	20.0	1253	375	5000/4625	790

15.5R20


A889

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A889	11.25	24PR	173	L	15.5	1260	440	6500	830

335/80R20MPT


A879

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A879	11.00	18PR	149	K	16.9	1044	340	3250	650

395/85R20


A889

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A889	10.00	14PR	158	M	19	1196	396	4250	660

425/85R21


A875

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A875	12.2-21	18PR	167	D	25	1260	425	5450	650

255/70R22.5


A852

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A852	7.50	16PR	140/137	N	10.5	930	255	2500/2300	830

11R22.5


A854


A803


A827



A825


A824


A801


A802


A809


A810


A832


A869


A844


A850


A884



A826


A867

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A854	8.25	18PR	151/148	G	20.4	1054	279	3450/3150	930
A803	8.25	20PR	152/149	M	17.0	1054	292	3550/3250	930
A827	8.25	18PR	151/148	K	15.5	1054	279	3450/3150	930
A825	8.25	16PR	146/143	M	15.5	1054	282	3000/2725	830
A824	8.25	16PR	146/143	M	10.5	1054	282	3000/2725	830
A801	8.25	18PR	151/148	K	14.5	1054	292	3450/3150	930
A802	8.25	18PR	151/148	K	18.5	1054	292	3450/3150	930
A809	8.25	18PR	151/148	G	20.5	1054	279	3450/3150	930
A810	8.25	18PR	151/148	G	20.5	1054	292	3450/3150	930
A832	8.25	18PR	151/148	K	19.5	1054	292	3450/3150	930
A869	8.25	20PR	152/149	K	17.0	1054	279	3550/3250	930
A844	8.25	20PR	152/149	K	20.0	1054	279	3550/3250	930
A850	8.25	18PR	151/148	K	18.0	1054	292	3450/3150	930
A884	8.25	18PR	151/148	K	20.5	1054	279	3450/3150	930
A826	8.25	16PR	146/143	L	20.5	1054	282	3000/2725	830
A867	8.25	18PR	151/148	K	23.0	1054	279	3450/3150	930

12R22.5


A854


A803


A827


A801


A807 PLUS


A809


A809 PLUS


A832


A869


A873


A890 PLUS


A849


A831


A877

12R22.5

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A854	9.00	18PR	152/149	G	18.5	1085	290	3350/3250	930
A803	9.00	18PR	152/149	K	17.0	1085	296	3550/3250	930
A827	9.00	18PR	152/149	L	17.0	1085	300	3550/3250	930
A801	9.00	18PR	152/149	K	14.5	1085	300	3550/3250	930
A807 PLUS	9.00	20PR	154/151	K	19.0	1085	300	3750/3450	970
A809	9.00	18PR	152/149	G	20.5	1085	300	3550/3250	930
A809 PLUS	9.00	18PR	152/149	F	25.0	1085	300	3550/3250	930
A832	9.00	18PR	152/149	K	20.5	1085	300	3550/3250	930
A869	9.00	20PR	156/153	K	17.5	1085	315	4000/3650	900
A873	9.00	20PR	154/151	F	25.0	1085	300	3750/3450	970
A890 PLUS	9.00	20PR	154/151	L	17.0	1085	300	3750/3450	970
A849	9.00	18PR	152/149	K	20.0	1085	300	3550/3250	930
A831	9.00	20PR	154/151	L	18.5	1085	300	3550/3250	970
A877	9.00	18PR	152/149	K	20.0	1085	300	3550/3250	930

13R22.5

























13R22.5

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A854	9.75	18PR	154/151	K	20.5	1124	309	3750/3450	830
A803	9.75	18PR	154/151	K	18.5	1124	331	3750/3450	830
A801	9.75	20PR	156/153	K	15.0	1124	331	3750/3450	830
A809	9.75	20PR	156/153	G	20.5	1124	331	4000/3650	830
A809 PLUS	9.75	22PR	158/156	G	20.5	1114	320	4250/4000	830
A832	9.75	18PR	154/151	K	19.5	1124	331	3750/3450	830
A869	9.75	20PR	156/153	K	17.0	1124	309	4000/3650	830
A869 PLUS	9.75	22PR	158/156	K	17.0	1124	320	4250/4000	830
A845	9.75	22PR	158/156	K	20.0	1124	320	4250/4000	830
A877	9.75	22PR	158/156	K	20.0	1124	320	4250/4000	830
A999	9.75	22PR	156/153	F	26.0	1132	320	4000/3650	930
A867	9.75	18PR	154/151	K	18.0	1124	320	3750/3450	900

275/70R22.5







PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A852	8.25	16PR	148/145	M	13.0	958	276	3150/2900	900
A809	8.25	16PR	148/145	G	20.5	958	274	3150/2900	900
A832	8.25	16PR	148/145	M	20.5	958	274	3150/2900	900

275/80R22.5



A855



A506

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A855	8.25	18PR	149/146	M	17.4	1018	276	3250/3000	900
A506	8.25	18PR	149/146	M	14.6	1012	276	3250/3000	900

295/75R22.5



A825



A822



A843



A826

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A825	9.00	16PR	146/143	M	15.5	1014	300	3000/2725	830
A822	9.00	16PR	146/143	M	10.5	1014	300	3000/2725	830
A843	9.00	16PR	146/143	L	20.5	1014	298	3000/2725	830
A826	9.00	16PR	146/143	L	20.5	1014	300	3000/2725	830



295/80R22.5


A854


AX865


A803


AX510


A827


A801


A802


A809


A832


A869


A887

295/80R22.5

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A854	9.00	18PR	152/149	G	19.0	1044	312	3550/3250	900
AX865	9.00	20PR	154/149	L	20.4	1050	298	3750/3250	900
A841 PLUS	9.00	20PR	154/150	L	16.5	1044	298	3750/3350	850
A800 PLUS	9.00	20PR	154/150	L	20.5	1050	298	3750/3350	850
A803	9.00	18PR	152/149	K	17.0	1044	312	3550/3250	900
AX510	9.00	20PR	154/149	L	16.4	1044	298	3750/3250	850
A827	9.00	20PR	154/150	L	17.0	1043	300	3750/3350	850
A801	9.00	18PR	152/149	K	15.5	1044	312	3550/3250	900
A802	9.00	18PR	152/149	K	18.5	1044	312	3550/3250	900
A809	9.00	18PR	152/149	G	20.5	1044	312	3550/3250	900
A832	9.00	18PR	152/149	K	19.5	1044	312	3550/3250	900
A869	9.00	20PR	154/150	L	17.0	1043	300	3750/3350	850
A887	9.00	20PR	154/150	G	20.5	1050	300	3750/3350	850

315/80R22.5


A854


A801


A801G+


A803


A701


A802


A823


A809


A809 PLUS


A813


A832


A869A


A869 PLUS


A872

315/80R22.5

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A854	9.00	20PR	157/154	J	23.0	1076	308	4125/3750	900
A841PLUS	9.00	22PR	158/156	K	16.5	1076	312	4250/4000	900
A800PLUS	9.00	22PR	158/156	K	20.5	1076	312	4250/4000	900
A801	9.00	20PR	157/154	K	17.0	1076	308	4125/3750	830
A801G+	9.00	20PR	157/154	K	15.0	1076	312	4125/3750	900
A803	9.00	20PR	157/154	K	17.0	1076	308	4125/3750	900
A701	9.00	20PR	157/154	K	15.0	1076	312	4125/3750	900
A802	9.00	20PR	157/154	K	18.5	1076	308	4125/3750	900
A823	9.00	20PR	157/154	K	14.5	1076	308	4125/3750	830
A809	9.00	20PR	157/154	G	20.5	1076	308	4125/3750	900
A809PLUS	9.00	22PR	158/156	G	21.0	1082	308	4250/4000	900
A813	9.00	20PR	157/154	K	17.5	1076	308	4125/3750	830
A823	9.00	20PR	157/154	K	19.5	1076	308	4125/3750	900
A869A	9.00	20PR	157/154	K	14.5	1076	308	4125/3750	900
A869 PLUS	9.00	22PR	158/156	K	17.0	1076	312	4250/4000	900
A872	9.00	20PR	157/154	K	15.0	1076	312	4125/3750	900

315/60R22.5


A802

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A802	9.75	18PR	152/148	L	17.9	950	313	3550/3150	900

385/65R22.5


A508


A806


A861


A861 PLUS


A836


A507


A805

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A508	11.75	20PR	160	K	16.0	1066	389	4500	900
A806	11.75	20PR	160	K	16.0	1072	392	4500	900
A861	11.75	20PR	160	K	15.5	1072	390	4500	900
A861 PLUS	11.75	24PR	164	K	16.5	1072	390	5000	900
A836	11.75	20PR	160	K	16.5	1072	390	4500	900
A507	11.75	24PR	164	J	17.4	1072	389	5000	930
A805	11.75	20PR	160	K	15.3	1072	390	4500	900

425/65R22.5


A503

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A503	12.25	20PR	165	J	15.9	1124	430	5150	825

325/95R24


A831


AX831


A505


A809


A809 PLUS


A877

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A831	9.00	22PR	162/160	K	15.9	1226	325	4750/4500	830
AX831	9.00	22PR	162/160	K	15.9	1226	325	4750/4500	830
A505	9.00	22PR	162/160	K	15.6	1228	325	4750/4500	850
A809	8.5	22PR	162/160	K	23.5	1232	314	4750/4500	850
A809 PLUS	8.5	22PR	162/160	K	23.5	1232	314	4750/4500	850
A877	8.5	22PR	162/160	K	20	1225	314	4750/4500	850

12.00R24





















12.00R24

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A801C	8.50	20PR	160/157	K	15.5	1226	306	4500/4125	900
A801	8.50	20PR	160/157	K	15.5	1226	312	4500/4125	900
A807	8.50	20PR	160/157	K	15.5	1208	306	4500/4125	900
A809	8.50	22PR	162/160	K	23.5	1232	314	4750/4500	850
A809 PLUS	8.50	22PR	162/160	K	23.5	1232	314	4750/4500	850
A829	8.50	20PR	160/157	K	18.0	1213	306	4500/4125	900
A817	8.50	20PR	160/157	K	20.0	1224	310	4500/4125	900
A582	8.50	20PR	160/157	K	18.0	1226	315	4500/4125	900
A814	8.50	24PR	164/161	L	32.0	1226	315	5000/4625	900
A877	8.50	22PR	162/160	K	20.0	1225	314	4750/4500	850

11R24.5











PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A825	8.25	16PR	149/146	M	15.5	1104	284	3250/3000	830
A822	8.25	16PR	149/146	M	10.5	1104	284	3250/3000	830
A843	8.25	16PR	149/146	L	20.5	1104	279	3250/3000	830
A809	8.25	16PR	149/146	G	20.5	1104	276	3250/3000	830
A826	8.25	16PR	149/146	L	20.5	1104	284	3250/3000	830

285/75R24.5









PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH (mm)	O.D (mm)	S.W (mm)	MAX LOAD (kg)	PRESSURE (kpa)
A825	8.25	16PR	147/144	M	15.5	1050	285	3075/2800	830
A822	8.25	16PR	147/144	M	10.5	1050	285	3075/2800	830
A843	8.25	16PR	147/144	L	24.5	1050	283	3075/2800	830
A826	8.25	16PR	147/144	L	20.5	1050	285	3075/2800	830

SUPERWAY

Revolutionary benefits

SIGNIFICANT IMPROVEMENTS

Rolling Resistance
Skid Resistance
Wear Resistance

MAXIMUM ENERGY EFFICIENCY

Use less and travel further

REDUCED CARBON EMISSIONS

Use more sustainable materials
and reduces fuel consumption

LOW-CARBON DEVELOPMENT

From raw materials,manufactu-ring
to product life cycle

MOLECULAR TECHNIQUES

Lmprove technological content

Through adopting a new tread formula design and the optimization of the molecular-level cross-linking network, making the rubber molecular segments more uniform and the frictional heat generation between the rubber and filler molecules is effectively reduced.The tire temperature is always kept at a relatively low level during driving so as to achieve a balance between high wear resistance and low rolling resistance.